

Samsung UDC Series Commercial LED LCD Displays

Thinner bezels. Larger impact.



ANGEL GROVE MALL DIRECTORY

1 LOWER LEVEL

2 MID LEVEL

Food & Beverage Burger Time Pizza Pizza Nice Cream Mr. Coffee Mambo Juice	Entertainment Regency Fun Center Bowl-O-Rama Jonah's Arcade	Specialty Vita Veeta Vitamins Pet World Milton Office Supplies Iris Eye Care	Apparel Fancy Footwear Adonis Athletics The Closet
---	---	---	--

MONDAY
 April 22 10:57 AM
77°F
 Partly Cloudy
 ↓ 22° 7:22 AM 76%
 ↑ 30° 7:17 PM 7 UV INDEX
 14-19 km/h FROM SW

Virtually Seamless Videowalls with Advanced Technology

Make sure all the attention is on your videowall, and not on the space in between. The Samsung UDC Series 46" and 55" displays feature a bezel-to-bezel width of just 5.5mm, to deliver impressive, high-resolution videowalls that are virtually seamless. Direct-lit LED technology delivers a rich, bright, 1920 x 1080 Full HD picture that commands attention, while being cost-efficient, as well as conserving energy. Advanced Color Calibration provides factory-calibrated color for precisely tuned Brightness, Color Temperature and Gamma. Deliver maximum impact with these premiere videowall displays. With the Samsung UDC Series commercial displays.

- 
Advanced Color Calibration
 UDC Series displays are factory tuned for Brightness, Color Temperature and Gamma. They deliver optimal uniformity and impressive images right out of the box.
- 
Advanced Color Management
 Fine-tune images through Samsung's new Advanced Color Management solution. A user-friendly interface makes detailed color adjustments simple (UD46C, UD55C models only).
- 
DisplayPort 1.2
 The DisplayPort 1.2 digital loop out feature allows you to easily share content across videowalls up to 10x10; including the ability to fully support Ultra High Definition resolution on 2x2 videowalls. It is an easy and cost-effective way to connect multiple displays.
- 
Sharp, Bright, Impactful
 Full HD 1920 x 1080 resolution and brightness levels of 700 nits (450 nits on UD46C-B) ensure a clear, vibrant videowall that's easy to look at and hard to ignore.
- 
Direct-Lit LED
 Direct-lit LED technology with a new backlight dimming solution allows the UDC Series display to achieve deeper blacks, higher contrast ratio of 3500:1, and power savings of up to 30%.
- 
Ultra-Slim Bezels, Virtually Seamless Videowalls
 The minimized bezel gap of just 5.5mm is crucial to the virtually seamless videowall experience that the UDC Series delivers. It's ideal for control rooms, the medical sector, conference rooms, broadcasting stations, transportation hubs, lobbies and retail.



Learn more ▶ 1-800-SAMSUNG | 1-866-SAM4BIZ | samsung.com/business or samsung.com/prodisplay
 Follow us: [@SamsungBizUSA](https://twitter.com/SamsungBizUSA) | [YouTube youtube.com/samsungbizusa](https://www.youtube.com/samsungbizusa)

Samsung UDC Series Commercial LED LCD Displays




KEY SPECIFICATIONS For complete product specifications, visit samsung.com/prodisplay

Display	Model Number	UD46C	UD55C	UD46C-B	UD55C-B
Screen Size		46" Direct-lit LED Backlit LCD	55" Direct-lit LED Backlit LCD	46" Direct-lit LED Backlit LCD	55"
Panel Technology		S-PVA (60Hz)	S-PVA (60Hz)	S-PVA (60Hz)	60Hz (Direct-LED Backlight)
Resolution		1920 x 1080 Full HD	1920 x 1080 Full HD	1920 x 1080 Full HD	1920 x 1080
Brightness		700 nits	700 nits	450 nits	500 nits
Contrast Ratio (Typical)		3500:1	3500:1	3500:1	3,500:1
Viewing Angle (Horizontal/Vertical)		178°/178°	178°/178°	178°/178°	178°/178°
Orientation		Landscape/Portrait	Landscape/Portrait	Landscape/Portrait	Landscape/Portrait
Response Time		8ms	8ms	6.5ms	8ms
Connectivity	Input	VGA (D-sub 15 pin), DVI-D, DisplayPort 1.2, Composite, HDMI (x2), Component, Stereo Mini Jack	VGA (D-sub 15 pin), DVI-D, DisplayPort 1.2, Composite, HDMI (x2), Component, Stereo Mini Jack	VGA (D-sub 15 pin), DVI-D, Composite, HDMI (x2), Component, Stereo Mini Jack	VGA (D-sub 15 pin), DVI-D, Composite, HDMI (x2), Component, Stereo Mini Jack
	Output	DisplayPort 1.2, Stereo Mini Jack	DisplayPort 1.2, Stereo Mini Jack	DVI-D (Loop out), Stereo Mini Jack	DVI-D (Loop out), Stereo Mini Jack
	External Control	RS232C (In/Out), RJ45	RS232C (In/Out), RJ45	RS232C (in/out), RJ45	RS232C (in/out), RJ45
	Response Time	Detachable Type (IR, Ambient)	Detachable Type (IR, Ambient)	Detachable Type (IR, Ambient)	Detachable Type (IR, Ambient)
Power	Power Supply	AC 100 - 240 V- (+/- 10 %), 50/60 Hz	AC 100 - 240 V- (+/- 10 %), 50/60 Hz	AC 100 - 240 V- (+/- 10 %), 50/60 Hz	AC 100 - 240 V- (+/- 10 %), 50/60 Hz
	Power Consumption (Typical/Max)	120W / 165W	160W / 220W	113W / 130W	150W / 165W
	Power Consumption (Standby)	< 0.5W	< 0.5W	< 0.5W	< 0.5W
Environmental Conditions	Operating Temperature	0°C - 40°C	0°C - 40°C	0°C - 40°C	0°C - 40°C
	Operating Humidity	10%~80%	10%~80%	10%~80%	10%~80%
Features	Special	Advanced Color Management, Magic Clone, Auto Source Switching & Recovery, Lamp Error Detection, Anti Retention (Haze 44%), Temperature Sensor, RS232C/RJ45 MDC, Plug and Play (DDC2B), PIP/PBP, Videowall (10x10), Pivot Display, Image Rotation, Button Lock, DP 1.2 Digital Daisy Chain (Supporting 2x2 UHD Resolution, HDCP Support), Smart Scheduling, Smart F/W update, Clock Battery (80 hrs. Clock Keeping), Built-in MagicInfo (Lite, Premium-S, VideoWall-S)	Advanced Color Management, Magic Clone, Auto Source Switching & Recovery, Lamp Error Detection, Anti Retention (Haze 44%), Temperature Sensor, RS232C/RJ45 MDC, Plug and Play (DDC2B), PIP/PBP, Videowall (10x10), Pivot Display, Image Rotation, Button Lock, DP 1.2 Digital Daisy Chain (Supporting 2x2 UHD Resolution, HDCP Support), Smart Scheduling, Smart F/W update, Clock Battery (80 hrs. Clock Keeping), Built-in MagicInfo (Lite, Premium-S, VideoWall-S)	Auto Source Switching & Recovery, Lamp Error Detection, Anti Retention (Haze 11%), Temperature Sensor, RS232C/RJ45 MDC, Plug and Play (DDC2B), PIP/PBP, Videowall (10x10), Pivot Display, Button Lock, DVI Digital Daisy Chain, Smart Scheduling, Smart F/W update, Clock Battery (80 hrs. Clock Keeping)	ACM Support (Advanced Color Management), Auto Source Switching & Recovery, Lamp Error Detection, Anti Retention, Temperature Sensor, RS232C/RJ45 MDC, Plug and Play (DDC2B), PIP/PBP, Videowall (10x10), Pivot Display, Button Lock, DP 1.2 Digital Daisy Chain (Supporting 2x2 UHD Resolution, HDCP Support), Smart Scheduling, Smart F/W update
	Tuner	N/A	N/A	N/A	N/A
	Internal Media Player	Cortex-A9 1GHz Dual Core, 1GB DDR3, 8GB FDM, USB (2)	Cortex-A9 1GHz Dual Core, 1GB DDR3, 8GB FDM, USB (2)	N/A	N/A
	VESA Standard Wall Mount Interface	600 x 400mm	600 x 400mm	600 x 400mm	600 x 400mm
Dimensions	Product Dimensions (without stand)	40.3" x 22.8" x 3.8"	47.8" x 27" x 3.8"	40.3" x 22.8" x 3.8"	47.8" x 27.0" x 4.5"
	Packaging Dimensions	49.4" x 31.4" x 14.0"	57.1" x 35.6" x 15.2"	49.4" x 31.4" x 14.0"	56.7" x 34.3" x 14.8"
	Bezel Width	3.5mm (U/L), 1.8mm (R/B)	3.7mm (U/L), 1.8mm (R/B)	3.7mm (U/L), 2.0mm (R/B)	3.7mm (U/L), 1.8mm (R/B)
Weight	Product Weight	40 lbs.	52.8 lbs.	40 lbs.	53.5 lbs.
	Shipping Weight	77 lbs.	91.5 lbs.	68.6 lbs.	77.2 lbs.
Service	Standard Warranty	3 Years On-Site (Parts / Labor / Backlight)	3 Years On-Site (Parts / Labor / Backlight)	3 Years On-Site (Parts / Labor / Backlight)	3 Years On-Site (Parts / Labor / Backlight)
Accessories	Included	Quick Setup Guide, Warranty Card, Application CD, D-sub Cable, Power Cord, Remote Controller, Batteries	Quick Setup Guide, Warranty Card, Application CD, D-sub Cable, Power Cord, Remote Controller, Batteries	Quick Setup Guide, Warranty Card, Application CD, D-sub Cable, Power Cord, Remote Controller, Batteries	Quick Setup Guide, Warranty Card, Application CD, D-Sub cable, Power Cord, Remote Controller, Batteries
	Optional Mount	WMN-4675MD	WMN-4675MD	WMN-4675MD	WMN-4675MD
	Optional Stand	MID-UD46FS	MID-UD55FS	MID-UD46FS	MID-UD55FS
	Optional Media Player	SBB-C, SBB-CD7, SBB-CQ7	SBB-C, SBB-CD7, SBB-CQ7	SBB-C, SBB-CD7, SBB-CQ7	SBB-C, SBB-CD7, SBB-CQ7
Green Management	Emission Standard	EMC	EMC	EMC	EMC
	ENERGY STAR® 6.0 Compliant	Yes	Yes	Yes	Yes
	RoHS Compliant	Yes	Yes	Yes	Yes
	Packaging Recyclability	Packing Materials Recyclable	Packing Materials Recyclable	Packing Materials Recyclable	Packing Materials Recyclable


CONNECTIVITY

1. RS232C Out
2. RS232C In
3. USB
4. IR Out
5. Control In
6. DisplayPort In
7. HDMI In 1
8. HDMI In 2
9. DisplayPort Out
10. DVI In
11. RGB In
12. AV/Comp
13. Audio In/Out
14. RJ45 In



CONNECTIVITY UD46C-B and UD55C-B Only

1. RS232C Out
2. RS232C In
3. Audio Out
4. IR Out
5. IR/Ambient Sensor In
6. RJ45 In
7. Component AV In
8. Audio In
9. VGA In
10. HDMI In 1
11. HDMI In 2
12. DVI In (MagicInfo)
13. DVI Out (Loopout)



For complete product information and accessories, visit samsung.com/business or samsung.com/prodisplay

Follow us: [@SamsungBizUSA](https://twitter.com/SamsungBizUSA) | [YouTube youtube.com/samsungbizusa](https://www.youtube.com/samsungbizusa)

Samsung Electronics has been named 2013 ENERGY STAR Partner of the Year in the product manufacturing category by the U.S. Environmental Protection Agency (EPA).



Product Support: 1-800-SAMSUNG
1-866-SAM4BIZ

©2013 Samsung Electronics America, Inc. Samsung is a registered mark of Samsung Electronics Corp., Ltd. Specifications and designs are subject to change without notice. Non-metric weights and measurements are approximate. All other brand, product, service names and logos are trademarks and/or registered trademarks of their respective manufacturers and companies. Simulated screen images. See samsung.com for detailed information. Printed in USA. LFD-UDCSEIESB2BDSHT-DEC13T

